

## Produktinformation DigiProtect



- Send and receive crisp video and audio wirelessly
- Allows remote color viewing on a compact hand-held LCD-Monitor
- Auto trigger function when detects enough voice

| <b>CMOS Kamera &amp; Sender /<br/>CMOS Camera &amp; Transmitter</b>             |   |
|---|---|
| <b>Bildsensor /<br/>Sensor</b>  | CMOS , 300.000 Pixel (VGA)  |
| <b>Übertragungsfrequenz /<br/>Transmit Frequency</b>                            | 2.400 GHz ~ 2.483 GHz   |
| <b>Übertragungsbereich /<br/>Transmit Range</b>                                 | 30 meter (offener Raum)<br>30 meters (open area)  |
| <b>Frequenzabweichung /<br/>Frequency Deviation</b>                             | +/- 100 Khz (10 C ~ 50 C)   |
| <b>Modulation /<br/>Demodulation Method</b>                                     | FM  |
| <b>RF Ausgangsleistung /<br/>RF Output Power</b>                                | Vcc = 5 V , Load =75 Ohm , 10 dBm   |
| <b>Antenne /<br/>Antenna</b>  | Dipol (85mm)  |
| <b>Mikrofon /<br/>Microphone</b>  | Internes Mikrofon<br>Build-in Microphone  |
| <b>Stromversorgung /<br/>Power Source</b>                                       | 6 V , Gleichstrom , 800 mA<br>6 V , DC , 800 mA   |
| <b>Stromverbrauch /<br/>Power Consumption</b>                                   | 720 mW  |
| <b>Betriebstemperatur /<br/>Operating Temperature</b>                           | 10°C – 50 °C  |
| <b>Kabelloser Monitor &amp; Empfänger /<br/>Wireless Monitor &amp; Receiver</b> |   |
| <b>Bildschirmgröße /<br/>Screen Size</b>  | 1,8" TFT LCD Monitor  |
| <b>Empfangsfrequenz /<br/>Receiver Frequency</b>                                | 2.400 ~ 2.483 GHz   |
| <b>Stromversorgung /<br/>Power Source</b>                                       | 6 V , Gleichstrom , 800 mA , oder 4 x AA Batterien<br>6 V DC , 800 MA , or 4 x AA Batteries   |
| <b>Stromverbrauch /<br/>Power Consumption</b>                                   | 2,3 W   |
| <b>Abmessungen /<br/>Dimension</b>  | 72 x 108 x 31 mm  |
| <b>Lieferumfang /<br/>Package Content</b>                                       | 1 CMOS-Kamera , 2 Netzteile (eine für Kamera , eine für Monitor) , 1 tragbarer LCD-Monitor ,<br>Bedienungsanleitung , 4 wiederaufladbare Batterien<br><br>1 CMOS camera , 2 Power Adapter (one for camera , one for LCD monitor) , 1 handheld LCD monitor ,<br>Users' Manual m 4 rechargeable batteries |

## Logistische Daten / Logistic Data

|  |                  |
|--|------------------|
| <b>Maße/Verpackung<br/>Dimension/Giftbox</b> | 253 x 232 x 75mm |
| <b>Gewicht/Verpackung<br/>Weight/Giftbox</b> | 1,40 kg          |
| <b>Inhalt/Karton /<br/>Pcs/carton</b>        | 10               |
| <b>Maße/Karton<br/>Dimension/carton</b>      | 476x380x255mm    |
| <b>Gewicht/Karton<br/>Weight/carton</b>      | 14,90 kg         |
| <b>EAN-Code</b>                              | 4719851871511    |
| <b>Artikel-Nummer</b>                        | 600010           |

[www.thiecom.de](http://www.thiecom.de)